

SMCWBR11S-3GN

150Mbps Wireless-N Mini 3G Broadband Router

Product Overview

SMCWBR11S-3GN is an all-in-one networking solution for connecting and sharing your high speed Internet connection. Designed to support a 3G USB Modem (not included), SMCWBR11S-3GN can act as your primary or secondary WAN connection. Convenient for those on the road, people living in areas that do not support xDSL/Cable, or those wanting auto-failover to ensure always-on service should xDSL/ Cable fail, SMCWBR11S-3GN provides the ultimate flexibility.

This platform combines 1 10/100Mbps LAN port, 1 10/100Mbps WAN port, a 802.11n access point providing up to 150Mbps high speed wireless connection, NAT firewall with SPI, a user friendly web-based management interface as well as Wi-Fi Protected Setup (WPS) that enables push button or PIN configuration in one convenient device.



Key Features and Benefits

Advanced, Robust Security

The SMCWBR11S-3GN NAT Firewall with Stateful Packet Inspection (SPI) to protect the internal host from hacker attacks. Wireless security is comprehensive and includes WPA/WPA2 PSK and Enterprise as well as a WPS button for the ultimate convenience of one touch secure connectivity.

Easy to Set up

The SMCWBR11S-3GN includes EZ Installation. Just insert the EZ installation CD follow the steps and start using your router in minutes.

Feature Rich

The SMCWBR11S-3GN has numerous features to meet your requirements including Wireless Distribution System (WDS), Dual SSIDs, Static Routing, Wi-Fi Multimedia (WMM) and more.

3G Connectivity

A USB 2.0 port permits sharing of a 3G modem's connectivity to the SMCWBR11S-3GN's LAN interface. (3G USB modem not included)













Application Diagram





Features

PHYSICAL

- One 10/100Mbps WAN port
- One 10/100Mbps LAN port
- One USB for 3G USB modem (not included)
- One external detachable 2 dBii antenna
- WPS button
- Reset button

MANAGEMENT FEATURES

- EZ Installation Wizard
- · Web-based management interface (HTTP)
- Remote management
- SNTP time synchronize

SECURITY FEATURES

- NAT Firewall with SPI
- Access Control
- MAC filter
- URL Blocking
- DMZ Host
- SSID Broadcast disable
- · Wireless MAC address Filtering
- WEP 64-/128-Bit Encryption
- WPA-/WPA2-PSK (Pre Shared Key)
- WPA/WPA2 Enterprise mode (802.1x)
- Wi-Fi Protected Setup (WPS)

ROUTER FEATURES

- Shared high speed 3G/cable/xDSL internet connection
- 1 10/100 LAN port with auto MDI-MDIX
- Built-in Wireless -N (802.11n) access point
- Static Routing
- NAT with ALGs
- 802.11e WMM
- IGMP Proxy
- Dual SSIDs

STANDARDS

• Wired: IEEE 802.3 (10Base-T)

IEEE 802.3u (100Base-TX)

• Wireless: IEEE 802.11b

IEEE 802.11g

IEEE 802.11n (draft 2.0)

OPERATING FREQUENCY

• FCC: 2412~2462MHz (Ch1~Ch11)

• ETSI: 2412~2472MHz (Ch1~Ch13)

• Japan: 2412~2484MHz (Ch1~Ch14)

TEMPERATURE

• Operating: 0°C to 40°C (32°F to 104°F)

 \bullet Storage: -20°C to 60°C (-4°F to 140°F)

HUMIDITY

• Operating: 10% to 85% Non-Condensing

• Storage: 5% to 90% Non-Condensing

DIMENSIONS

93 x 70 x 26mm

UPGRADE METHOD

Web

WEIGHT

74g

POWER REQUIREMENTS

• Input Voltage: 100V AC to 240V AC, 50 / 60Hz

• Output Power: 12V DC, 1A

TX Output Power

- 11g/n without antenna 14 dBm +- 1 dBm
- 11b without antenna 17 dBm +- 1 dBm

SYSTEM REQUIREMENTS

- Broadband 3G Internet service with USB 2.0 modem connection, or Cable/xDSL Internet service and modem with Ethernet connection
- 2.4GHz 802.11n draft wireless adapter or 2.4GHz 802.11b/g wireless adapter installed on each PC. Alternatively an Ethernet adapter can be used.
- Internet Explorer 5.5 or above, Mozilla Firefox 1.0 or above
- We recommend using this product with the SMCWCB-N2, SMCWPCI-N2 and SMCWUSB-N wireless adapters

PACKAGE CONTENTS

- SMCWBR11S-3GN
- Power adapter: 12V, 1A
- RJ45 cable
- QIG
- CD with EZ Installation + Documentation
- Warranty information card

WARRANTY

Please check <u>www.smc.com</u> for the warranty terms in your country/region

Contact

North America 20 Mason, Irvine, CA 92618, U.S.A. 1-800-SMC-4YOU 24/7 Technical Support

Europe/Africa Fructuos Gelabert 6-8 08970 Sant Joan Despi Barcelona, Spain

SMC Networks Asia Pacific 1 Coleman Street #07-09, The Adelphi Singapore 179803

Tel: 65-63387667 Fax: 65-63387767

Taiwan

No. 1 Creation Rd, III, Science-based Industrial Park, Hsinchu 30077, Taiwan, R.O.C.

Tel: +886 3 5770270 Fax: +886 3 5780764

Check www.smc.com for your local country contact information

©2009 SMC Networks. BarricadeTM is a trademark of SMC Networks. Other trademarks or registered trademarks are the property of their respective owners. Information is subject to change without notice. All rights reserved.